

DATA SHEET

CL3 is CLAD-LINE's subframe system for mechanically secret fixed applications, suitable for use with Rockpanel, high-pressure laminate (HPL), ceramic, thin stone and fibre cement.

CLAD-LINE's CL3 panel hangers which are secured to the rear face of the cladding panel simply 'hook-on' to the horizontal rails. The CL3 horizontal rails can be fixed back to the CL1, CL4 or CLF2F systems.



Material:

CL Rails: Aluminium Grade 6063 T6 (mill finish)

CL Support Brackets: Aluminium Grade 6063 T6 (mill finish)

CL3 Rails: Aluminium Grade 6063 T6 (mill finish)

CL3 Hangers: Aluminium Grade 6063 T6 (mill finish)

Fire Performance:

CL Rails: A1 Reaction to Fire Classification to EN13501

CL Support Brackets: A1 Reaction to Fire Classification to EN13501 (Iso Pad – exempt under Regulation 7 (3) i of the Building Regulations Approved Document B*

CL3 Rails: A1 Reaction to Fire Classification to EN13501

CL3 Hangers: A1 Reaction to Fire Classification to EN13501

*Building Regulations Approved Document B (Fire Safety) volume 1: Dwellings, 2019 editions incorporating 2020 amendments PLUS June 2022 amendments to Approved Document B, volume 1 and volume 2